

## CA-530

### Camera Adaptor for BVP-950/950P/550/570

- Analog component output via CCZ 26-pin VTR interface
- SDI output via CCZ 26-pin VTR interface
- SDI output via BNC connector
- Convenient facilities for stand alone portable operation
- MIC Input
- Power Save Mode
- Light Weight and Compact design with low power consumption
- Optional viewfinder (BVF-55/55CE) can be attached

Supplied accessories: Operation manual (1)  
Maintenance manual (1)  
Cable holder (1)  
Screw M3\*6 (4)  
Battery spacer (1)

### Specifications

#### General

Power requirements: DC 12V (10.5V to 17V)  
Power consumption: 6W  
Operating temperature: -20°C to +45°C (-4°F to +113°F)  
Storage temperature: -20°C to +45°C (-4°F to +113°F)  
Mass: Approx. 2.0kg (4 lb 7 oz)

#### Connectors

##### Input/output

SDI OUT: BNC, 0.8Vp-p, 75Ω  
MIC IN: XLR-3-pin (Female), 600Ω, balanced  
DC IN: XLR-4-pin (Male), 10.5V to 17V  
DC OUT: 4-pin, 10.5V to 17V, maximum current DC 0.2A  
GENLOCK IN: BNC, 1.0Vp-p, 75Ω  
MONITOR OUT: BNC, 1.0Vp-p, 75Ω  
EARPHONE: Mini jack, 8Ω  
CAMERA I/F: 68-pin (2)  
VTR: 26-pin (CCZ type)  
RCP: 8-pin (Female)

